

L Number	Hits	Search Text	DB	Time stamp
1	2	("6014122") or ("5453757")).PN.	USPAT; US-PPGPUB	2003/05/16 15:59
2	1252	345/89	USPAT; US-PPGPUB	2003/05/16 15:59
3	100	345/89 and reference near5 (direct\$2 amplifier\$1 buffer\$1)	USPAT; US-PPGPUB	2003/05/16 16:44
4	952	reference adj2 voltage and buffer\$1	EPO; JPO	2003/05/16 16:38
6	19	((reference adj2 voltage and buffer\$1) and switch\$3) and (display\$1 screen\$1 gr\$1y adj scale)	EPO; JPO	2003/05/16 16:39
7	0	(reference adj2 voltage and buffer\$1) and by\$1pass adj2 (driver\$1 buffer\$1)	EPO; JPO	2003/05/16 16:44
8	1	345/89 and by\$1pass\$3 adj buffer\$1	USPAT; US-PPGPUB	2003/05/16 16:45
5	302	(reference adj2 voltage and buffer\$1) and switch\$3	EPO; JPO	2003/05/16 16:49
-	2101	(345/204,690,211,212).CCLS.	USPAT; US-PPGPUB	2003/05/16 15:06
-	2701	(345/55,77,87,89,94,95).CCLS.	USPAT; US-PPGPUB	2003/05/16 15:08
-	4464	((345/204,690,211,212).CCLS.) ((345/55,77,87,89,94,95).CCLS.)	USPAT; US-PPGPUB	2003/05/16 15:08
-	783	((345/204,690,211,212).CCLS.) ((345/55,77,87,89,94,95).CCLS.)) and reference adj2 voltage	USPAT; US-PPGPUB	2003/05/16 15:09
-	283	((345/204,690,211,212).CCLS.) ((345/55,77,87,89,94,95).CCLS.)) and reference adj2 voltage) and buffer\$1	USPAT; US-PPGPUB	2003/05/16 16:38
-	27	((((345/204,690,211,212).CCLS.) ((345/55,77,87,89,94,95).CCLS.)) and reference adj2 voltage) and buffer\$1) and low\$2 adj3 impedance	USPAT; US-PPGPUB	2003/05/16 15:10